

ACCESSORI

■ STANDARD □ OPTIONAL

DESCRIPTION	REX PF	NOTE
Standard colors: BLU RAL 5005 and SILVER RAL 7040	■	
Nr. 1 standard platform with electrostatics galvanized smooth staves	■	
Max. Travel 2500 mm.	■	
Nr. 2 bases for pit fixing	■	
Nr. 2 lifting cylinders	■	
Nr. 2 "Dead man present" push button boards with keys on the floors IP 65	■	
Security control module for sensors and safety locks	■	
Nr. 1 hydraulic pump with motor	■	
Nr. 1 electrical panel board	■	
Standard power supply 230-400 V/3Ph/50 - 460 V/3Ph/60 Hz	■	
Nr. 2 stopping wheel	■	
2 stops	■	
Safety Electromechanical locks	■	
Nylon package	■	
Screws anchors	■	
Platform with non standard measures	□	
Standard platform with hot dip galvanized staves (standard measures)	□	
Additional cost for platform with non standard hot dip galvanized staves	□	
Bearing wheel for intensive use	□	Advisable for over 10 cycles / day
Additional stop (third stop)	□	
Additional push button board	□	
Push button board design style	□	
Push button board in stainless steel	□	
Additional electromagnetic sensor	□	
Additional electric lock	□	For manual doors control
Predisposition for Kronenberg or Prudhomme electric lock	□	For manual doors control
Outside pulse recall for each push button board	□	Applicable just on enclosed shaft
Pulse command return to home position button (just with pulse manouver)	□	Applicable just on enclosed shaft
Automatic repositioning to the floor (only with pulse manouver)	□	Applicable just on enclosed shaft
Remote control - each receiver	□	Max. ray 5 mt
Remote control - each transmitter	□	Complete with support columns
Flashing light	□	
Siren	□	
2 colors trafic light (Red/ Green)	□	
2 colors trafic light (Red/ Green) design style	□	
Waterproof galvanized cover for control unit for outdoor installation	□	
Soft Starter	□	
Hydraulic pump with low acoustic emission	□	
Emergency descent maneuver with manual pump	□	On request
Nr. 1 fix handrail H=1200 mm (per meter)	□	
Nr. 1 removable handrail H=1200 mm (per meter)	□	
Nr. 2 photocells barrier car for forward and backward control H=600 mm	□	
Nr. 2 photocells barrier car for forward and backward control H= 900 mm	□	Complete with support columns
Photocell barrier for door's area control H=150 mm	□	Complete with support columns
Photocell barrier for door's area control H=300 mm	□	
Laser scanner for area control	□	
Kit nr. 4 ground supports	□	
Non standard power supply	□	
Non standard colour	□	On request
Interpon bottom + varnishing	□	
Additional cost for Interpon bottom + non standard platform varnishing	□	
Hot dip galvanization	□	
Additional cost for non standard hot dip galvanized platform	□	Platform, scissors and bases
Platform staves on pallet	□	
Control unit on wooden crate	□	