

# DOUBLE SPACER 25/2

|                    | Tragkraft          | Standardhub | Standard-Hebebühne  | Abstand der Hebebühne | Grube      | Leistung | Hoch- / Runterfahrzeit | Versorgung    | Standardgewicht | Hinweise |
|--------------------|--------------------|-------------|---------------------|-----------------------|------------|----------|------------------------|---------------|-----------------|----------|
| DOUBLE SPACER 25/2 | 2 + 2<br>x2500 kg. | 1910<br>mm  | 4600 x 5200<br>mm   | 1810<br>mm            | 2110<br>mm | 3 kw     | 64 / 64 s              | 400 v / 50 hz | 3950kg.         |          |
|                    | 2 + 2<br>x5512 lbs | 75,2 inch   | 181,1x204,7<br>inch | 71,3<br>inch          | 83,1 inch  | 5,5 hp   | 64 / 64 s              | 400 v / 50 hz | 8700 lbs        |          |
| DOUBLE SPACER 25/2 | 2 + 2<br>x2500 kg. | 1910<br>mm  | 4800 x 5200<br>mm   | 1810<br>mm            | 2110<br>mm | 3 kw     | 64 / 64 s              | 400 v / 50 hz | 4050 kg.        |          |
|                    | 2 + 2<br>x5512 lbs | 75,2 inch   | 189,1x204,7<br>inch | 71,3<br>inch          | 83,1 inch  | 5,5 hp   | 64 / 64 s              | 400 v / 50 hz | 8921 lbs        |          |
| DOUBLE SPACER 25/2 | 2 + 2<br>x2500 kg. | 1910<br>mm  | 5000 x 5200<br>mm   | 1810<br>mm            | 2110<br>mm | 3 kw     | 64 / 64 s              | 400 v / 50 hz | 4150 kg.        |          |
|                    | 2 + 2<br>x5512 lbs | 75,2 inch   | 196,9x204,7<br>inch | 71,3<br>inch          | 83,1 inch  | 5,5 hp   | 64 / 64 s              | 400 v / 50 hz | 9141 lbs        |          |
| DOUBLE SPACER 25/2 | 2 + 2<br>x2500 kg. | 1910<br>mm  | 5200 x 5200<br>mm   | 1810<br>mm            | 2110<br>mm | 3 kw     | 64 / 64 s              | 400 v / 50 hz | 4250 kg.        |          |
|                    | 2 + 2<br>x5512 lbs | 75,2 inch   | 204,7x102,4<br>inch | 71,3<br>inch          | 83,1 inch  | 5,5 hp   | 64 / 64 s              | 400 v / 50 hz | 9361 lbs        |          |